

THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A displacement sensor for a substance dispensing device having a translating piston, the sensor comprising:
 - a. a plunger rod coupled to the piston bearing an encoded pattern of encoding features;
 - b. a light source for illuminating the encoded pattern;
 - c. a detector array for detecting light from the illuminated encoded pattern and generating a detector signal; and
 - d. a processor for determining a displacement of the plunger rod relative to a fiducial reference position based at least on the detector signal at any time during dispensing.
2. (Original) A displacement sensor according to claim 1, wherein the encoding features are regions of modulated optical transmission through the plunger rod.
3. (Original) A displacement sensor according to claim 1, wherein the encoding features are regions of modulated optical reflection by the plunger rod.
4. (Original) A displacement sensor according to claim 1, wherein the encoding features are a plurality of slots of enhanced transmission through the plunger rod.
5. (Original) A displacement sensor according to claim 4, wherein each slot is displaced from each pair of nearest neighbors by a unique combination of distances.
6. (Original) A displacement sensor according to claim 4, wherein the combination of any two adjacent spaces between slots uniquely identifies a characteristic of the reservoir.
7. (Original) A displacement sensor according to claim 6, wherein the identified characteristic of the reservoir is a displacement relative to a fiducial position.
8. (Original) A displacement sensor according to claim 6, wherein the identified characteristic of the reservoir is content of a reservoir to which the plunger rod pertains.

9. (Original) A displacement sensor according to claim 6, wherein the identified characteristic of the reservoir includes at least one of diameter and wall composition material.
10. (Original) A displacement sensor according to claim 1, wherein the light source includes an optical diffuser for illuminating a region of the plunger rod with substantially uniform optical intensity.
11. (Original) A displacement sensor according to claim 1, wherein the encoded pattern of encoding features repeats along the plunger rod.
12. (Currently Amended) A dispensing apparatus comprising:
 - a. a reservoir having a cylindrical inner volume for containing a substance;
 - b. a plunger rod for impelling a piston along a linear axis of motion within the inner volume of the reservoir in order to displace and dispense a measured quantity of the substance;
 - c. an encoding pattern of encoding features disposed along the plunger rod in a direction parallel to the linear axis of motion of the piston;
 - d. a detector array for detecting light from the illuminated encoded pattern and generating a detector signal; and
 - e. a processor for determining a displacement of the plunger rod relative to a fiducial reference position based at least on the detector signal at any time during dispensing.
13. (Original) A dispensing apparatus according to claim 12, wherein the encoding features are regions of modulated optical transmission through the plunger rod.
14. (Original) A dispensing apparatus according to claim 12, wherein the encoding features are a plurality of slots of enhanced transmission through the plunger rod.
15. (Previously Present) A dispensing apparatus according to claim 14, wherein each slot is displaced from the pair of nearest neighbors by a unique combination of distances.
16. (Original) A dispensing apparatus according to claim 12, having more than 1 reservoir version, wherein the encoding pattern is uniquely determinative of a version of the reservoir.
17. (Currently Amended) A method for measuring a rate of dispensing a substance by means of a dispenser having a piston driven along an axis of motion within a reservoir of the substance, the method comprising:

- a. illuminating an encoded pattern of encoding features disposed upon a plunger rod coupled to the piston;
- b. detecting light from the illuminated encoding features and generating a detector signal; and
- c. determining a displacement of the plunger rod relative to a fiducial reference position based at least on the detector signal at any time during dispensing.

18. (Original) A method according to claim 17, wherein the step of detecting light further includes acquiring an image of the illuminated encoding features.

19. (Original) A method according to claim 17, wherein the step of determining a displacement further includes determining positions of peaks of light transmission through the encoding features.

20. (Original) A method according to claim 17, further including the step of storing each successive detector array value in each of successive groups of n software array elements.